

560 Blower Package



The MAC 560 Series of vacuum style blower packages are configured around the size and performance of the blower to optimize performance. Line sizes from 2" to 8" are covered by the 6 models in this series. The silencers are premium grade chambered design for maximum noise reduction. A wide variety of blowers manufactured by Roots, Sutorbilt and Duroflow are available with this package.

Standard Specifications

- Positive displacement blower
- Table top base (painted)
- Adjustable motor base
- V-belt drive
- Belt guard
- Relief valve
- Inter-connecting hardware
- Discharge silencer (absorptive type)
- Combination inlet filter/silencer
- Vacuum gauge
- All blowers are rated for 15" Hg maximum
- All blower volumes are based on standard inlet conditions (14.7 PSIA, 70° F)
- MAC white paint standard

Options:

- Vacuum switch (NEMA 4, NEMA 7/9 and dual settings available)
- Temperature gauge
- Temperature switch
- Galvanized base
- Expansion joints
- Sanitary base design
- Tachometer
- Acoustically treated guard and silencers
- Vibration isolators
- If noise levels must be guaranteed at less than 90 dBa, a sound enclosure or acoustic treated components will be necessary

Dimensions (IN.)

MODEL	A	B	C	D	E	F	G	H	J	K	L	WT. (LBS.)
562	2	25 ³ / ₁₆	31 ¹³ / ₁₆	35	30	42	13 ³ / ₈	74 ³ / ₄	51 ¹ / ₈	51	10 ¹ / ₈	1025
563	3	25 ³ / ₁₆	31 ¹³ / ₁₆	45 ¹ / ₂	33 ¹ / ₂	42	13 ³ / ₈	73 ³ / ₁₆	50 ¹ / ₁₆	50	10 ¹ / ₈	1225
564	4	25 ³ / ₁₆	31 ¹³ / ₁₆	50 ¹ / ₂	33 ¹ / ₂	42	13 ³ / ₈	72 ³ / ₈	49 ¹ / ₈	52 ³ / ₁₆	10 ¹ / ₈	1625
565	5	25 ³ / ₁₆	31 ¹³ / ₁₆	50 ¹ / ₂	40	53	14 ¹ / ₈	74 ⁵ / ₁₆	50 ³ / ₁₆	64 ¹ / ₂	11 ¹ / ₈	1700
566	6	25 ³ / ₁₆	31 ¹³ / ₁₆	55	40	59	15 ¹ / ₈	79 ¹ / ₄	51 ¹ / ₈	70 ¹¹ / ₁₆	11 ¹ / ₈	2325
568	8	36 ⁷ / ₁₆	43 ¹ / ₁₆	65	45	83	17 ³ / ₁₆	90 ⁹ / ₁₆	63 ³ / ₈	94 ³ / ₄	12 ¹ / ₈	3400

