

# MAC2vent

*The new MAC2vent is a compact design bin vent that is capable of large air volumes. It's low profile, top access cartridge removal, and no ladder access makes it the ideal candidate for silos, belt conveyor transfer points, and other hard to access applications. The MAC2vent incorporates a pulse cleaning mechanism with integral timing controller. The MAC2vent comes with the most efficient cartridges on the market. Models range from 2, 4, & 6 cartridge units that will handle airflow's from 500 cfm to 3800 cfm.*

## Features:

- Heavy-duty 12 ga. Construction.
- 26" long cartridges with 255 ft<sup>2</sup> media each.
- Insertable or plenum style housing available.
- Sloped roof to promote run-off.
- 180° F construction.
- Magnehelic gauge standard.
- Pre-plumbed timer in a NEMA 4 enclosure mounted on compressed air header standard.
- Quick cartridge change-out.
- Various media options available.
- Side mount fans optional.



MODEL	TOTAL SQ. FT. OF MEDIA	NUMBER OF CARTRIDGES	CU. FT. PER PULSE	A	B	C	D	E	F	G	EST. WT. LBS.
				W2V2	510	2	1.3	22 1/4	25 1/4	5	
W2V4	1020	4	2.4	40	43	8	5 3/16	32	50 7/16	51 15/16	620
W2V6	1530	6	3.4	57 3/4	60 3/4	12	4 15/16	40	68 3/16	69 11/16	840

